



# Shell Catenex Oil S 920

## Paraffinic Process Oil

Shell Catenex Oils S are paraffinic process oils manufactured via the solvent extraction process. They are general purpose process oils used as extender or carrier fluids.

### DESIGNED TO MEET CHALLENGES

#### Specifications, Approvals & Recommendations

For a full listing of equipment approvals and recommendations, please consult your local Shell Technical Helpdesk.

#### Typical Physical Characteristics

Properties			Method	Shell Catenex Oil S 920
Colour (ASTM)			ASTM D1500	0.5
Density	@15°C	kg/m <sup>3</sup>	ISO 12185	859
Refractive Index	@20°C		ASTM D1218	1.472
Flashpoint (COC)		°C	ISO 2592	200
Pour Point		°C	ISO 3016	-15
Kinematic Viscosity	@20°C	mm <sup>2</sup> /s	ISO 3104	40
Kinematic Viscosity	@40°C	mm <sup>2</sup> /s	ISO 3104	17
Kinematic Viscosity	@100°C	mm <sup>2</sup> /s	ISO 3104	3.7
Sulphur (X-Ray)		% m/m	ISO 14596	0.15
Carbon Type Distribution : C/A (S-corr.)		%	DIN 51378/ASTM D2140 mod.	2
Carbon Type Distribution : C/N (S-corr.)		%	DIN 51378/ASTM D2140 mod.	33
Carbon Type Distribution : C/P (S-corr.)		%	DIN 51378/ASTM D2140 mod.	65
Refractive Intercept (RI)			DIN 51378	1.0442
Viscosity Gravity Constant (VGC)			DIN 51378	0.813
Aniline Point		°C	ISO 2977	99
Clay Gel Analysis : Polar Components		% m/m	ASTM D2007	0.1
Clay Gel Analysis : Aromatic Components		% m/m	ASTM D2007	13.9
Clay Gel Analysis : Saturated Components		% m/m	ASTM D2007	86.0
Evaporation Loss (22 hrs)	@107°C	% m/m	ASTM D972	2
Noack Volatility (1 hr)	@250°C	% m/m	ASTM D5800	39
PCA Content (DMSO Method)		% m/m	IP 346	<3

These characteristics are typical of current production. Whilst future production will conform to Shell's specification, variations in these characteristics may occur.

#### Health, Safety & Environment

##### • Health and Safety

Shell Catenex Oil S 920 is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Material Safety Data Sheet, which can be obtained from <http://www.epc.shell.com/>

- **Protect the Environment**

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.

### **Additional Information**

- **Advice**

Advice on applications not covered here may be obtained from your Shell representative.