SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

| Trade name | : Shell Catenex Oil S 323 |
|--------------|---------------------------|
| Product code | : 901L2658 |
| CAS-No. | : 64742-54-7 |

1.2 Relevant identified uses of the substance or mixture and uses advised against

| Recommended restrictions | : | This product must not be used in applications other than those |
|--------------------------|---|--|
| on use | | listed in Section 1 without first seeking the advice of the sup- |
| | | plier. |

1.3 Details of the supplier of the safety data sheet

| Company | : | Shell & Turcas Petrol A.Ş. Salih Tozan Sk.No:18bblk Esentepe-Sisli 34394 Istanbul |
|--|---|---|
| Telephone | : | +902124441502 |
| Telefax | : | +902123760600 |
| E-mail address of person responsible for the SDS | : | If you have any enquiries about the content of this SDS please email lubricantSDS@shell.com |
| Emergency telephone numbe | r | |
| Emergency telephone num- ber | : | 0212 376 00 00 |

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification T.R. SEA No 28848

Not a hazardous substance or mixture.

Classification T.R. SAE No 27092

Not a hazardous substance or mixture according to EC-directives 67/548/EEC or 1999/45/EC.

2.2 Label elements

Labelling T.R. SEA No 28848

Hazard pictograms : No symbol

Signal word

: No signal word

Signal wo

1.4

SAFETY DATA SHEET Prepared according to the regulation on Safety Data Sheets regarding Hazardous substances and mixtures (R.G. 13/12/2014-29204).

Shell Catenex Oil S 323

Initial release date: 12.05.2010 Revision Date: 29.05.2015 Version 1.4 MSDS Number: 800001015887

| Hazard statements | : | PHYSICAL HAZARDS: Not classified as a physical hazard accord- ing to CLP criteria. HEALTH HAZARDS: Not classified as a health hazard under CLP criteria. ENVIRONMENTAL HAZARDS: Not classified as environmental hazard according to CLP criteria. |
|--------------------------|---------------|---|
| Precautionary statements | : Prevention: | No precautionary phrases. |
| | Response: | No precautionary phrases. |
| | Storage: | |
| | Disposal: | No precautionary phrases. |
| | | No precautionary phrases. |

2.3 Other hazards

The substance does not fulfill all screening criteria for persistence, bioaccumulation and toxicity and hence is not considered to be PBT or vPvB. Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis. Used oil may contain harmful impurities. Not classified as flammable but will burn.

SECTION 3: Composition/information on ingredients

| 3.2 Mixtures | |
|--------------|--|
|--------------|--|

Chemical nature

: Highly refined mineral oil. The highly refined mineral oil contains <3% (w/w) DMSOextract, according to IP346.

Hazardous components

SECTION 4: First aid measures

| 4.1 Description of first aid measu | res |
|------------------------------------|--|
| General advice | : Not expected to be a health hazard when used under normal conditions. |
| Protection of first-aiders | : When administering first aid, ensure that you are wearing the appropriate personal protective equipment according to the |

| | incident, injury and surroundings. |
|--------------------------------|---|
| If inhaled | : No treatment necessary under normal conditions of use. If symptoms persist, obtain medical advice. |
| In case of skin contact | Remove contaminated clothing. Flush exposed area with wa- ter and follow by washing with soap if available. If persistent irritation occurs, obtain medical attention. |
| In case of eye contact | : Flush eye with copious quantities of water. If persistent irritation occurs, obtain medical attention. |
| If swallowed | : In general no treatment is necessary unless large quantities are swallowed, however, get medical advice. |
| 4.2 Most important symptoms an | d effects, both acute and delayed |
| Symptoms | : Oil acne/folliculitis signs and symptoms may include formation of black pustules and spots on the skin of exposed areas. Ingestion may result in nausea, vomiting and/or diarrhoea. |

4.3 Indication of any immediate medical attention and special treatment needed

Treatment

: Notes to doctor/physician: Treat symptomatically.

SECTION 5: Firefighting measures

| 5.1 | Extinguishing media Suitable extinguishing media | : | Foam, water spray or fog. Dry chemical powder, carbon dio- xide, sand or earth may be used for small fires only. |
|-----|---|----|---|
| | Unsuitable extinguishing media | : | Do not use water in a jet. |
| 5.2 | Special hazards arising from t | he | e substance or mixture |
| | Specific hazards during fire- fighting | : | Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide may be evolved if incomplete combustion occurs. Unidentified organic and inorganic compounds. |
| 5.3 | Advice for firefighters | | |
| | Special protective equipment for firefighters | : | Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in |

| | a confined space. Select fire fighter's clothing approved to relevant Standards (e.g. Europe: EN469). |
|----------------------------|---|
| Specific extinguishing me- | : Use extinguishing measures that are appropriate to local cir- |
| thods | cumstances and the surrounding environment. |

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

| Personal precautions | Pe | rsonal | precautions |
|----------------------|----|--------|-------------|
|----------------------|----|--------|-------------|

: Avoid contact with skin and eyes.

6.2 Environmental precautions

| - | Environmental precautions | : | Use appropriate containment to avoid environmental contami- nation. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers. |
|---|---------------------------|---|---|
| | | | Local authorities should be advised if significant spillages cannot be contained. |

6.3 Methods and material for containment and cleaning up

| Methods for cleaning up | Slippery when spilt. Avoid accidents, clean up immediately. Prevent from spreading by making a barrier with sand, earth or other containment material. Reclaim liquid directly or in an absorbent. Soak up residue with an absorbent such as clay, sand or other suitable material and dispose of properly. |
|-------------------------|---|
| | |

6.4 Reference to other sections

For guidance on selection of personal protective equipment see Chapter 8 of this Safety Data Sheet., For guidance on disposal of spilled material see Chapter 13 of this Safety Data Sheet.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

| Technical measures | : Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material. |
|-------------------------|---|
| Advice on safe handling | Avoid prolonged or repeated contact with skin. Avoid inhaling vapour and/or mists. When handling product in drums, safety footwear should be worn and proper handling equipment should be used. Properly dispose of any contaminated rags or cleaning mate- rials in order to prevent fires. |

7.2 Conditions for safe storage, including any incompatibilities

| Other data | Keep container tightly closed and in a cool, well-ventilated place. Use properly labeled and closable containers. |
|-------------------------|---|
| | Store at ambient temperature. |
| | Refer to section 15 for any additional specific legislation cov- ering the packaging and storage of this product. |
| Packaging material | Suitable material: For containers or container linings, use mild steel or high density polyethylene. Unsuitable material: PVC. |
| 7.3 Specific end use(s) | |
| Specific use(s) | Please refer to Ch16 and/or the annexes for the registered uses under REACH. |
| | Not applicable |

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

| Components | CAS-No. | Value type (Form of exposure) | Control parameters | Basis |
|-------------------|---------|-------------------------------|--------------------|--|
| Oil mist, mineral | | TWA | 5 mg/m3 | US. ACGIH Threshold Limit Values |

Biological occupational exposure limits

No biological limit allocated.

8.2 Exposure controls

Engineering measures

The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include:

Adequate ventilation to control airborne concentrations.

Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.

General Information:

Define procedures for safe handling and maintenance of controls. Educate and train workers in the hazards and control measures relevant to normal activities as-

SAFETY DATA SHEET Prepared according to the regulation on Safety Data Sheets regarding Hazardous substances and mixtures (R.G. 13/12/2014-29204). Shell Catenex Oil S 323

Initial release date: 12.05.2010 Revision Date: 29.05.2015 Version 1.4 MSDS Number: 800001015887

sociated with this product.

Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.

Drain down system prior to equipment break-in or maintenance.

Retain drain downs in sealed storage pending disposal or subsequent recycle.

Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

Personal protective equipment

| Eye protection | If material is handled such that it could be splashed into eyes, protective eyewear is recommended. |
|--------------------------|--|
| Hand protection | |
| Remarks | Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. PVC, neoprene or nitrile rubber gloves Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended. |
| | For continuous contact we recommend gloves with break- through time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same, but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is de- pendent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model. |
| Skin and body protection | Skin protection is not ordinarily required beyond standard work clothes. It is good practice to wear chemical resistant gloves. |
| Respiratory protection : | No respiratory protection is ordinarily required under normal conditions of use. In accordance with good industrial hygiene practices, precautions should be taken to avoid breathing of material. If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specification. |
| 14 | 800001015887 TR |

| | | ic conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are suitable, select an appropri- ate combination of mask and filter. Select a filter suitable for the combination of organic gases and vapours [Type A/Type P boiling point >65°C (149°F)]. |
|----------------------------|-----|--|
| Protective measures | : | Personal protective equipment (PPE) should meet recom- mended national standards. Check with PPE suppliers. |
| Environmental exposure con | tro | bls |
| General advice | : | Take appropriate measures to fulfill the requirements of rele- vant environmental protection legislation. Avoid contamination of the environment by following advice given in Chapter 6. If necessary, prevent undissolved material from being dis- charged to waste water. Waste water should be treated in a municipal or industrial waste water treatment plant before discharge to surface water. Local guidelines on emission limits for volatile substances must be observed for the discharge of exhaust air containing |

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

| Appearance | : Liquid at room temperature. |
|--|--|
| Colour | : clear |
| Odour | : Slight hydrocarbon |
| Odour Threshold | : Data not available |
| рН | : Not applicable |
| pour point | : -15 °C Method: ISO 3016 |
| | |
| Initial boiling point and boiling range | : > 280 °C estimated value(s) |
| ••••••••••••••••••••••••••••••••••••••• | |
| range | estimated value(s) : 210 °C |
| range Flash point | estimated value(s) : 210 °C Method: ISO 2592 |
| range Flash point Evaporation rate | estimated value(s) : 210 °C Method: ISO 2592 : Data not available |

vapour.

SAFETY DATA SHEET Prepared according to the regulation on Safety Data Sheets regarding Hazardous substances and mixtures (R.G. 13/12/2014-29204). Shell Catenex Oil S 323

Initial release date: 12.05.2010 Revision Date: 29.05.2015 Version 1.4 MSDS Number: 800001015887

| Lower explosion limit | : Typical 1 %(V) |
|--|---|
| Vapour pressure | : < 0,5 Pa (20 °C) estimated value(s) |
| Relative vapour density | : > 1 estimated value(s) |
| Density | : 866 kg/m3 (15,0 °C) Method: ISO 12185 |
| Solubility(ies) | |
| Water solubility | : negligible |
| Solubility in other solvents | : Data not available |
| Partition coefficient: n- octanol/water | : Pow: > 6 (based on information on similar products) |
| Auto-ignition temperature | : > 320 °C |
| Viscosity | |
| Viscosity, dynamic | : Data not available |
| Viscosity, kinematic | : 4,6 mm2/s (100 °C) Method: ISO 3104 |
| | 24,5 mm2/s (40,0 °C) Method: ISO 3104 |
| | 61 mm2/s (20 °C) Method: ISO 3104 |
| 9.2 Other information | |
| Conductivity | : This material is not expected to be a static accumulator. |
| Decomposition temperature | : Data not available |

SECTION 10: Stability and reactivity

10.1 Reactivity

The product does not pose any further reactivity hazards in addition to those listed in the following

| sub-paragraph. | |
|---------------------------------------|--|
| 10.2 Chemical stability | |
| Stable. | |
| 10.3 Possibility of hazardous | reactions |
| Hazardous reactions | : Reacts with strong oxidising agents. |
| 10.4 Conditions to avoid | |
| Conditions to avoid | : Extremes of temperature and direct sunlight. |
| 10.5 Incompatible materials | |
| Materials to avoid | : Strong oxidising agents. |
| 10.6 Hazardous decompositio | on products |
| · · · · · · · · · · · · · · · · · · · | - |

Hazardous decomposition products are not expected to form during normal storage.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

| Acute toxicity | |
|---------------------------------|---|
| Product: Acute oral toxicity | : LD50 (rat): > 5.000 mg/kg |
| | Remarks: Expected to be of low toxicity: |
| Acute inhalation toxicity | : LC 50 (Rat): > 5 mg/l Exposure time: 4 h Remarks: Low toxicity by inhalation. |
| Acute dermal toxicity | : (Rabbit): Remarks: Low toxicity: LD50 > 5000 mg/kg |

Skin corrosion/irritation

Product:

Remarks: Not irritating to skin. Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.

Serious eye damage/eye irritation

Product:

Remarks: Expected to be non-irritating to eyes.

Respiratory or skin sensitisation

Product:

Remarks: Not expected to be a skin sensitiser.

Germ cell mutagenicity

Product:

Genotoxicity in vivo

: Remarks: Not considered a mutagenic hazard.

Carcinogenicity

Product:

Remarks: Not expected to be carcinogenic.

Remarks: Product contains mineral oils of types shown to be non-carcinogenic in animal skinpainting studies.

Highly refined mineral oils are not classified as carcinogenic by the International Agency for Research on Cancer (IARC).

| Material | GHS/CLP Carcinogenicity Classification |
|----------------------------|--|
| Highly refined mineral oil | No carcinogenicity classification. |

Reproductive toxicity

Product:

Effects on fertility

Remarks: Not expected to impair fertility. Not expected to be a developmental toxicant.

STOT - single exposure

Product:

Remarks: Not expected to be a hazard.

STOT - repeated exposure

Product:

Remarks: Not expected to be a hazard.

Aspiration toxicity

Product:

Not considered an aspiration hazard.

Further information

Product:

Remarks: Used oils may contain harmful impurities that have accumulated during use. The concentration of such impurities will depend on use and they may present risks to health and the environment on disposal.

ALL used oil should be handled with caution and skin contact avoided as far as possible.

Remarks: Slightly irritating to respiratory system.

SECTION 12: Ecological information

12.1 Toxicity

| <u>Product:</u> Toxicity to fish (Acute toxic- ity) | Remarks: Expected to be practically non toxic _L/EL/IL50 > 100 mg/l | C : |
|---|--|---------------|
| Toxicity to daphnia and other aquatic invertebrates (Acute toxicity) | Remarks: Expected to be practically non toxic _L/EL/IL50 > 100 mg/l | 2: |
| Toxicity to algae (Acute toxic- ity) | Remarks: Expected to be practically non toxic _L/EL/IL50 > 100 mg/l | D: |
| Toxicity to fish (Chronic toxic- ity) | Remarks: NOEC/NOEL expected to be > 10 | - <= 100 mg/l |
| Toxicity to daphnia and other aquatic invertebrates (Chron-ic toxicity) | Remarks: NOEC/NOEL expected to be > 10 | - <= 100 mg/l |
| Toxicity to bacteria (Acute toxicity) | Remarks: Expected to be practically non toxic _L/EL/IL50 > 100 mg/l | o: |

12.2 Persistence and degradability

Product:

| Biodegradability | : Remarks: Expected to be inherently biodegradable. |
|------------------|---|
|------------------|---|

12.3 Bioaccumulative potential

12.4 Mobility in soil

Product:

| Mobility : | Remarks: Liquid under most environmental conditions., If it enters soil, it will adsorb to soil particles and will not be mobile. |
|---------------------------------------|---|
| | Remarks: Floats on water. |
| 12.5 Results of PBT and vPvB asse | ssment |
| Product: | |
| Assessment : | The substance does not fulfill all screening criteria for persis- tence, bioaccumulation and toxicity and hence is not consi- dered to be PBT or vPvB |
| 12.6 Other adverse effects | |
| Product: | |
| Additional ecological informa- : tion | Remarks: Product is a mixture of non-volatile components, which are not expected to be released to air in any significant quantities. |
| | Not expected to have ozone depletion potential, photochemi- cal ozone creation potential or global warming potential. |
| | Remarks: Films formed on water may affect oxygen transfer and damage organisms. |
| | May cause physical fouling of aquatic organisms. |
| | Remarks: Mineral oil is not expected to cause any chronic effects to aquatic organisms at concentrations less than 1 mg/l. |

SECTION 13: Disposal considerations

13.1 Waste treatment methods

| Product | : Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment. Waste, spills or used product is dangerous waste. |
|------------------------|---|
| Contaminated packaging | : Dispose in accordance with prevailing regulations, preferably to a recognized collector or contractor. The competence of the collector or contractor should be established beforehand. Disposal should be in accordance with applicable regional, national, and local laws and regulations. |

SECTION 14: Transport information

14.1 UN number

Not regulated as a dangerous good

Shell Catenex Oil S 323

Initial release date: 12.05.2010 Revision Date: 29.05.2015 Version 1.4 MSDS Number: 800001015887

14.2 UN proper shipping name

Not regulated as a dangerous good

14.3 Transport hazard class(es)

Not regulated as a dangerous good

14.4 Packing group

Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Remarks

: Special Precautions: Refer to Chapter 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport.

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

| Product name Special precautions Additional Information | Not applicable Not applicable MARPOL Annex 1 rules apply for bulk shipments by sea. |
|---|---|
| Pollution category | : Not applicable |
| Ship type | : Not applicable |
| Product name | : Not applicable |

SECTION 15: Regulatory information

| 15.1 Safety, health and environmental regulations/legislation specific for the substance or mix- ture | | |
|--|--|--|
| Other regulations | : Regulations on the health and safety precautions for chemi- cals in the workplace. Regulations on the fire protection of buildings. Regulations on the prevention of industrial acci- dents and the reduction of their effects. | |
| The components of this product are reported in the following inventories: | | |
| EINECS | : All components listed or polymer exempt. | |
| TSCA | : All components listed. | |

SECTION 16: Other information

| SDS Author Name, Surname | : Eda Demirer | |
|-----------------------------|---|------|
| Address | : Shell & Turcas Petrol A.Ş. Derince Tesisleri Deniz Mah. P.O Cad. | |
| | 00 | 0004 |

SAFETY DATA SHEET Prepared according to the regulation on Safety Data Sheets regarding Hazardous substances and mixtures (R.G. 13/12/2014-29204). Shell Catenex Oil S 323

Initial release date: 12.05.2010 Revision Date: 29.05.2015 Version 1.4 MSDS Number: 800001015887

| 41900 Derince-Kocaeli |
|---|
| : 25 May 2015 |
| : GBF-1921 |
| A vertical bar () in the left margin indicates an amendment from the previous version. Revision changes: Revised according to regulation on Safety Data Sheets (SDSs) regarding hazardous substances and mixtures (R.G. 13/12/2014-29204) |
| |

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

TR / EN